



PRODUCTION INSTRUCTION OF PO - 1844 / AO-S E-3 / RT-17066 (REVERSIBLE)

DESCRIPTION	60*100	70*110	80*150	45*50	50*90	90*160	75*75
Party Quality	2200	2200	2200	2200	2200	2200	2200
Party Weight	1.321	1.692	2.638	.495	.990	3.167	.970
Production Quality	2420	2420	2420	2420	2420	2420	2420
Production Weight	1.453	1.863	2.900	.544	1.090	3.487	1.068
Pile Height - A							
Pile Height - B							
Pile Height - C							
Stitching 10 Cm A							
Stitching 10 Cm B							
Stitching 10 Cm C							
Width in Line 5 cms							
Niddle Gape / Weaving Com							
1. Yarn UV/Non UV							
2. Canvas UV/Non UV	ANUVA CANVAS	ANUVA CANVAS	ANUVA CANVAS	ANUVA CANVAS	ANUVA CANVAS	ANUVA CANVAS	ANUVA CANVAS
3. Canvas Size	70	70	70		70	70	70
4. Canvas Quality							
5. Canvas Weight @ PC.							
6. Canvas Cutting Size							
7. Pipen Tanki Fold							
8. Stiching in 5 CMS							
9. Pipen Folder MM							
10. Latex							
11. Export Packing							

12. Carving							
TUMBLER / WASHING							
PC DYEING WEIGHT	1.421	1.821	2.837	.532	1.065	3.409	1.044
PC WASHING WEIGHT							
TUMBLING WEIGHT							
TUFFTING FINAL WEIGHT							
EXTRA WORK WEIGHT							
ORDER QUANTITY	393	263	138	659	448	178	183